

# VX-Pi1000GB-60

*DC-DC IEEE 802.3bt Gigabit High PoE Injector 24-56V DC*



## Product Description

The Versa Technology VX-Pi1000GB-60 is an IEEE 802.3bt Power Over Ethernet Injector which provides DC 48V over Ethernet cables. Versa Technology has developed a new Single-Port PoE+ Injector which meets the requirements of both the IT and security industry for high wattage output and easy installation.

## PoE with High Power, Security, Stability and Easy Installation Features

The VX-Pi1000GB-60 is a single-port Gigabit 802.3bt PoE+ injector with internal power supply in compact housing. Carrying both Ethernet data and power simultaneously, the VX-Pi1000GB-60 helps users to utilize just one Ethernet cable to easily install and deploy IP cameras, wireless AP's or VoIP phone networks in environments where power outlets are hard to find.

The PoE in-line power following the IEEE 802.3bt Power over Ethernet Plus standard makes the VX-Pi1000GB-60 able to deliver Gigabit speed Ethernet data and up to 60 watts of power to remote PoE compliant powered devices (PDs) over one Cat.5E/6 Ethernet cable. The VX-Pi1000GB-60 provides more flexible power requirements for all kinds of PDs at affordable installation costs.

### Features:

- 2-port RJ45 interfaces: 1 Data + Power output, 1 Data input
- DC power In: 24-56VDC
- IEEE 802.3bt pre-compliant
- Backward compatible with IEEE 802.3af/at Power over Ethernet
- Supports up to 75 watts PoE
- Auto-detection of PoE IEEE 802.3bt devices that could be damaged by incorrect installation
- Remote power feed up to 100m

# Specifications

Interface	<ul style="list-style-type: none"> <li>• 1 x RJ45 Data In Port</li> <li>• 1 x RJ45 PoE Out Port</li> </ul>
Network Cable	<ul style="list-style-type: none"> <li>• 10BASE-T: 2-pair UTP Cat. 3, 4, 5, up to 100M (328ft)</li> <li>• 100BASE-TX: 2-pair UTP Cat. 3, 4, 5, up to 100M (328ft)</li> <li>• 1000BASE-T: 2-pair UTP Cat. 5, 5e, 6 up to 100M (328ft)</li> <li>• EIA/TIA-568 100-ohm STP (100m)</li> </ul>
Data Rate	<ul style="list-style-type: none"> <li>• 10/100/1000Mbps</li> </ul>
Input Voltage	<ul style="list-style-type: none"> <li>• 24-56 VDC, 24-56 VDC Nominal Voltage</li> </ul>
Input Current	<ul style="list-style-type: none"> <li>• 3.0Arms max.</li> </ul>
Inrush Current	<ul style="list-style-type: none"> <li>• 30Amps max. (Cold start at 48VDC input with rated load and 25°C ambient)</li> </ul>
Power Output	<ul style="list-style-type: none"> <li>• Voltage: 48 VDC</li> <li>• Load: 0A - 1.25W</li> <li>• Peak: 1.3-2.5A</li> </ul>
Load/Line Regulation	<ul style="list-style-type: none"> <li>• Voltage: 48 VDC</li> <li>• Min Voltage: 48V</li> <li>• Max. Voltage: 48.8V</li> <li>• Line Regulation: <math>\pm 3\%</math></li> <li>• Load Regulation: <math>\pm 2\%</math></li> </ul>
Ripple & Noise	<ul style="list-style-type: none"> <li>• 200mVp-p (@48VDC)</li> </ul>
Power Requirements	<ul style="list-style-type: none"> <li>• 24 ~ 56 VDC</li> </ul>
Power Consumption	<ul style="list-style-type: none"> <li>• 75 watts max.</li> </ul>
PoE Standard	<ul style="list-style-type: none"> <li>• IEEE 802.3af/at/bt Ultra PoE PSE</li> </ul>

## PoE Power Output

- DC 48V / 60 watts

## Dimensions (L x W x H)

- 123 x 60 x 39mm

## Weight

- TBA

## Environment Temperature

- Operating Temperature: -10° ~ 40° C
- Storage Temperature: -20° ~ 85° C

## Relative Humidity

- 5 ~ 90% relative humidity, 72 hours, full load normal operation

## Standards Compliance

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- IEEE 802.3ab 1000BASE-T Gigabit Ethernet
- IEEE 802.3af Power over Ethernet
- IEEE 802.3at High Power over Ethernet Plus
- IEEE 802.3bt 4-pair Power over Ethernet

## Regulatory Compliance

- UL

# VX-Pi1000GB-60

DC-DC IEEE 802.3bt Gigabit High PoE Injector 24-56V DC



The Versa Technology VX-Pi1000GB-60 is an IEEE 802.3bt Power Over Ethernet Injector which provides DC 48V over Ethernet cables. Versa Technology has developed a new Single-Port PoE+ Injector which meets the requirements of both the IT and security industry for high wattage output and easy installation.

The PoE in-line power following the IEEE 802.3bt Power over Ethernet Plus standard makes the VX-Pi1000GB-60 able to deliver Gigabit speed Ethernet data and up to 60 watts of power to remote PoE compliant powered devices (PDs) over one Cat.5E/6 Ethernet cable. The VX-Pi1000GB-60 provides more flexible power requirements for all kinds of PDs at affordable installation costs.

## Features:

- 2-port RJ45 interfaces: 1 Data + Power output, 1 Data input
- DC power In: 24-56 VDC
- IEEE 802.3bt compliant
- Backward compatible with IEEE 802.3af/at Power over Ethernet
- Supports up to 60 watts PoE
- Auto-detection of PoE IEEE 802.3bt devices that could be damaged by incorrect installation
- Remote power feed up to 100m

## Specifications:

<b>Data Rate</b>	10/100/1000Mbps	<b>Power Requirements</b>	24~56 VDC
<b>Input Voltage</b>	24-56 VDC	<b>Power Consumption</b>	60W max.
<b>Input Current</b>	3.0Arms max.	<b>PoE Standard</b>	IEEE 802.3bt Ultra PoE PSE
<b>Inrush Current</b>	30Amps max.	<b>PoE Power Output</b>	DC 48V / 60W
<b>Output Power</b>	60W	<b>Dimensions (L x W x H)</b>	123 x 60 x 39mm
<b>Output Voltage</b>	48 VDC	<b>Operating Temperature</b>	-10° ~ 40° C
<b>Line Regulation</b>	±3%	<b>Storage Temperature</b>	-20° ~ 85° C
<b>Load Regulation</b>	±2%	<b>Relative Humidity</b>	5 ~90% RH, 72hrs. Full Load
<b>Ripple &amp; Noise</b>	200mVp-p (@48VDC)	<b>Regulatory Compliance</b>	UL

### Data In Pins      Data & Power Out Pins

1	—————	1 -Power
2	—————	2 -Power
3	—————	3 +Power
4	—————	4 +Power
5	—————	5 +Power
6	—————	6 +Power
7	—————	7 -Power
8	—————	8 -Power